




Powerful, clean solutions with a stainless reputation.

Industry-leading features and unparalleled support make Cone Drive's stainless reducer suitable for the most sterile manufacturing environments and equipped to withstand the most caustic washdown operations.

PACKAGING | FOOD & BEVERAGE | PHARMACEUTICAL | MEAT & DAIRY

**MADE IN
USA**

Just introduced!



NEMA Product Support:

- Industry-leading lead times
- Configuration & rating tools for 3D models and tested & verified ratings
- 5-year warranty
- Modifications & customizations
- Immediate engineering and sales support

NEMA Double Reduction

NEMA Single Reduction


 **CONFIGURE & DOWNLOAD YOUR MODEL AT** [ConeTools.com](https://conetools.com)




S P E C I F I C A T I O N S

- Double reduction solutions now available for system design flexibility and thermal capacity superiority: high ratio and high efficiency options
- Reducer and custom options available with standard quill & non-fretting bushing
- Stainless Steel housing (316) and Stainless Steel (304) solid, hollow, or shrink disk output options in inch or metric
- Feet, flanges, or direct mounting for universal positioning
- Dual input bearing and true double enveloping gearing for superior rigidity and torque density
- Lifetime food-grade lubrication, suited for temperatures from -10° to 200°F (-23° to 93°C)
- Double input & output seals with material upgrades available, and o-ring equipped adaptation
- IP69K and NSF rated, tested, and approved hygienic design

Sizes Available	1.54, 1.75, 1.97, 2.38, 3.00 in (39, 44, 50, 60, 76 mm)
Ratios	5:1 to 600:1, custom
Backlash Range	4 to 24 arcmin (.07 to 0.40°)
Input Speed	<1750 RPM
Input Power	<14 HP (10 kW)
Output Torque	<7000 lb-in (800 Nm)
Efficiency	<92%



 **Cone Drive Operations, Inc.**
240 East 12th Street
Traverse City, MI 49684, USA

 +1.888.994.2663
 orders@conedrive.com
 conedrive.com




Powerful, clean solutions with a stainless reputation.

Industry-leading features and unparalleled support make Cone Drive's stainless reducer suitable for the most sterile manufacturing environments and equipped to withstand the most caustic washdown operations.

PACKAGING | FOOD & BEVERAGE | PHARMACEUTICAL | MEAT & DAIRY

**MADE IN
USA**



Servo Product Support:

- Industry-leading lead times
- Configuration & rating tools for 3D models and tested & verified ratings
- 5-year warranty
- Modifications & customizations
- Immediate engineering and sales support

Servo Single Reduction

CONFIGURE & DOWNLOAD YOUR MODEL AT [ConeTools.com](https://conetools.com)

S P E C I F I C A T I O N S

- Reducer and custom options available with zero-backlash coupling connections
- Stainless Steel housing (316) and Stainless Steel (304) solid, hollow, or shrink disk output options in inch or metric
- Feet, flanges, or direct mounting for universal positioning
- Dual input bearing and true double enveloping gearing for superior rigidity and torque density
- Lifetime food-grade lubrication, suited for temperatures from -10° to 200°F (-23° to 93°C)
- Double input & output seals with material upgrades available, and o-ring equipped adaptation
- IP69K and NSF rated, tested, and approved hygienic design

Sizes Available	1.54, 1.75, 1.97, 2.38, 3.00 in (39, 44, 50, 60, 76 mm)
Ratios	5:1 to 60:1, custom
Backlash Range	4 to 24 arcmin (.07 to 0.40°)
Input Speed	<3000 RPM
Efficiency	<92%
$T_{\text{accel-in}}$	<900 lb-in (100 Nm)
$T_{\text{accel-out}}$	<6400 lb-in (700 Nm)

NSF



Cone Drive Operations, Inc.
240 East 12th Street
Traverse City, MI 49684, USA

+1.888.994.2663
 orders@conedrive.com
 conedrive.com